```
L11 ANSWER 23 OF 41 CA COPYRIGHT 2008 ACS on STN
AN
    120:251887 CA
OREF 120:44471a,44474a
ED Entered STN: 14 May 1994
   Extrusion of cement-based building materials
IN
    Tsugi, Yasushi
    Kubota Kk, Japan
Jpn. Kokai Tokkyo Koho, 4 pp.
PA
SO
    CODEN: JKXXAF
DT
    Patent
LA
    Japanese
    ICM C04B028-02
    ICS B28B003-20
ICI C04B028-02, C04B014-06, C04B016-02, C04B024-38, C04B024-22, C04B022-06,
    C04B016-08, C04B014-16
    58-4 (Cement, Concrete, and Related Building Materials)
FAN.CNT 1
                                                                   DATE
                                            APPLICATION NO.
    PATENT NO.
                        KIND
                               DATE
                                -----
                                            _____
     -----
                                            JP 1992-189940
                                                                   19920623
                                19940111
                         Α
    JP 06001648
                                19980402
                         B2
    JP 2736206
PRAI JP 1992-189940
                                19920623
CLASS
                CLASS PATENT FAMILY CLASSIFICATION CODES
 PATENT NO.
               ----
                       C04B028-02
 JP 06001648
                ICM
                ICS
                       B28B003-20
                        C04B028-02, C04B014-06, C04B016-02, C04B024-38,
                 ICI
                        C04B024-22, C04B022-06, C04B016-08, C04B014-16
                        C04B0028-02 [ICM,5]; B28B0003-20 [ICS,5]; C04B0028-02
                 IPCI
                        [ICI,5]; C04B0028-00 [ICI,5,C*]; C04B0014-06 [ICI,5]; C04B0016-02 [ICI,5]; C04B0024-38 [ICI,5]; C04B0024-22
                        [ICI,5]; C04B0024-00 [ICI,5,C*]; C04B0022-06 [ICI,5];
                        C04B0022-00 [ICI,5,C*]; C04B0016-08 [ICI,5];
                        C04B0016-00 [ICI,5,C*]; C04B0014-16 [ICI,5];
                        C04B0014-02 [ICI,5,C*]
                        B28B0003-20 [I,C*]; B28B0003-20 [I,A]; C04B0028-00 [I,C*]; C04B0028-02 [I,A]
                 IPCR
                        C04B028/02
                 ECLA
     In the extrusion of compns. comprising cement, SiO2
    powder (0.7-1.3 weight parts/weight part cement), reinforcing fibers,
     lightwt. aggregate, and an extrusion aid, 0.1-3 weight% (based on
    the the above mixture) salt of naphthalenesulfonic acid-H2CO condensate and
    3-15 weight% Mg(OH)2 are added to the mixture and then water is mixed to be
     extruded. A mixture prepared from cement 40, sand 53,
     cellulose pulp 7, foamed polystyrene beads 0.85, Me
     cellulose 0.6, and water 50 weight parts, with addition of Mighty 150
    3.0, and Mg(OH)2 5-10 weight parts, was extruded and cured first at
     30° for 15 h and then autoclaved at 6.7 kg/cm2 for 8 h to give
     smooth boards having bending strength 101 kg/cm2.
     plasticizer magnesium hydroxide cement
ST
```